

Performance Data of Swimming Pool Heat Pump Unit



Verticle : Gas Type -R407C

PH-02630-R407C

Power Supply		V/PH/Hz	220/1/50
YL-H01-Heating : A24/W26C	Heating Capacity	KW	14
		BTU/H	47768
	Power Input	KW	2.5
	Current	A	11.6
YL-H02-Heating : A35/W30C	Heating Capacity	KW	11.9
		BTU/H	40603
	Power Input	KW	2.6
	Current	A	12
YL-C01-Cooling : A35/W30C	Cooling Capacity	KW	9
		BTU/H	30708
	Power Input	KW	2.4
	Current	A	11.1
YL-C02-Cooling : A46/W30C	Cooling Capacity	KW	7.7
		BTU/H	26102
	Power Input	KW	2.6
	Current	A	11.7
Operating	Water Outlet Temp Range	C	5~40
	Amblent Temp Range	C	-10~53
	Compressor Type		Scroll*1
	Controller		Micro Processor Based Digital Controller with LED Touch Screen Display
	Noise	dB(A)	50
Heating Exchanger	Type		Titanium/PVC
	Standard Water Flow	m3/h	6
	Sugestion Water Flow	m3/h	4~8
	Water Pressure Drop (Max)	kPa	11
	Water pipe		-
	Water Connection	mm	50
Fan	Fan Position		Verticle
	Material		Plastic
Dimension	Net	mm	706/686/940
	Shipping	mm	755/740/1090
Weight		kg	125/135