

Performance Data of Swimming Pool Heat Pump Unit



Verticle : Gas Type -R407C

PH-02712-R407C

Power Supply		V/PH/Hz	380/3/50
YL-H01-Heating : A24/W26C	Heating Capacity	KW	45
		BTU/H	153540
	Power Input	KW	8.2
	Current	A	14.6
YL-H02-Heating : A35/W30C	Heating Capacity	KW	38.3
		BTU/H	130509
	Power Input	KW	8.5
	Current	A	15.2
YL-C01-Cooling : A35/W30C	Cooling Capacity	KW	36
		BTU/H	122832
	Power Input	KW	9.4
	Current	A	16.7
YL-C02-Cooling : A46/W30C	Cooling Capacity	KW	30.6
		BTU/H	104407
	Power Input	KW	9.9
	Current	A	17.8
Operating	Water Outlet Temp Range	C	5~40
	Ambient Temp Range	C	-10~53
	Compressor Type		Scroll*2
	Controller		Micro Processor Based Digital Controller with LED Touch Screen Display
	Noise	dB(A)	59
Heating Exchanger	Type		Titanium/PVC
	Standard Water Flow	m3/h	19.3
	Sugestion Water Flow	m3/h	13~26
	Water Pressure Drop (Max)	kPa	15
	Water pipe		PPR or PVC
	Water Connection	mm	63
Fan	Fan Position		Verticle
	Material		Plastic
Dimension	Net	mm	1450/705/1065
	Shipping	mm	1525/780/1210
Weight		kg	260/280