

Performance Data of Swimming Pool Heat Pump Unit



Verticle : Gas Type -R407C

PH-02713-R407C

Power Supply		V/PH/Hz	380/3/50
YL-H01-Heating : A24/W26C	Heating Capacity	KW	50
		BTU/H	170600
	Power Input	KW	9.1
	Current	A	16.3
YL-H02-Heating : A35/W30C	Heating Capacity	KW	42.5
		BTU/H	145010
	Power Input	KW	9.4
	Current	A	16.9
YL-C01-Cooling : A35/W30C	Cooling Capacity	KW	43
		BTU/H	146716
	Power Input	KW	11.3
	Current	A	20.2
YL-C02-Cooling : A46/W30C	Cooling Capacity	KW	36.6
		BTU/H	124709
	Power Input	KW	12
	Current	A	21.5
Operating	Water Outlet Temp Range	C	5~40
	Ambient Temp Range	C	-10~53
	Compressor Type		Scroll*2
	Controller		Micro Processor Based Digital Controller with LED Touch Screen Display
	Noise	dB(A)	59
Heating Exchanger	Type		Titanium/PVC
	Standard Water Flow	m3/h	21.5
	Sugestion Water Flow	m3/h	15~29
	Water Pressure Drop (Max)	kPa	16
	Water pipe		PPR or PVC
	Water Connection	mm	63
Fan	Fan Position		Verticle
	Material		Plastic
Dimension	Net	mm	1450/705/1265
	Shipping	mm	1525/780/1410
Weight		kg	265/285