

Performance Data of Swimming Pool Heat Pump Unit



Verticle : Gas Type -R407C

PH-02760-R407C

Power Supply		V/PH/Hz	380/3/50
YL-H01-Heating : A24/W26C	Heating Capacity	KW	210
		BTU/H	716520
	Power Input	KW	38.2
	Current	A	68.3
YL-H02-Heating : A35/W30C	Heating Capacity	KW	178.5
		BTU/H	609042
	Power Input	KW	39.7
	Current	A	70.9
YL-C01-Cooling : A35/W30C	Cooling Capacity	KW	158
		BTU/H	539096
	Power Input	KW	41.6
	Current	A	74.3
YL-C02-Cooling : A46/W30C	Cooling Capacity	KW	134.3
		BTU/H	458232
	Power Input	KW	44.2
	Current	A	79
Operating	Water Outlet Temp Range	C	5~40
	Ambient Temp Range	C	-10~53
	Compressor Type		Scroll*8 or 4
	Controller		Micro Processor Based Digital Controller with LED Touch Screen Display
	Noise	dB(A)	65
Heating Exchanger	Type		Titanium/PVC
	Standard Water Flow	m3/h	90.3
	Sugestion Water Flow	m3/h	60~120
	Water Pressure Drop (Max)	kPa	32
	Water pipe		PPR or PVC
	Water Connection	mm	110
Fan	Fan Position		Verticle
	Material		Plastic
Dimension	Net	mm	2200/1615/1355
	Shipping	mm	2260/1710/1520
Weight		kg	1200/1250